

DS

Directional Spots



3D page



Directional Spot

DS1300BK/BZ

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Optional cowling thumb set screw - allowing downlight use
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DS1300BK
 - (BZ) Bronze - DS1300BZ
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 6.25" L x 2.5" W



DS1300BK



DS1300BZ



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS1300BK/BZ-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS1300BK-LXC2 and DS1300BZ-LXC2 include:
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DS1300BK
 - (BZ) Bronze - DS1300BZ
 - GS1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 6.25" L x 2.5" W



DS1300BK



DS1300BZ



LXC2-MR16

Directional Spot

DS2100WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 5.25" L x 2.125" W



DS2100WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2100WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2100WB-LXC2 includes:
 - DS2100WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700k
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.125" W



DS2100WB



LXC2-MR16

Directional Spot

DS2160WB/CB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- (CB) Carbon Black
 - CB cast brass fixtures finished with a superior top quality Dupont polyester powder coating
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 5.25" L x 2.125" W




DS2160CB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2160WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2160WB-LXC2 includes:
 - DS2160WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700k
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.125" W



DS2160WB



Intertek



LXC2-MR16

Directional Spot

DS2300WB/CB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- (CB) Carbon Black
 - CB cast brass fixtures finished with a superior top quality Dupont polyester powder coating
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 5.25" L x 2.5" W



DS2300WB



DS2300CB



Intertek



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2300WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2300WB-LXC2 includes:
 - DS2300WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 Year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.5" W



DS2300WB



Intertek



LXC2-MR16



“I-LED” – Integrated LED

Universal Lighting Systems strives for innovative design. Designing “I-LED” products to superior quality standards improved lifespan, light source optimization, and dimming.

UNVLS - crafting value through innovation.

Directional Spot

DS2600WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Adjustable / removable cowling for discrete lighting
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 5.25" L x 2.5" W



DS2600WB



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2600WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2600WB-LXC2 includes:
 - DS2600WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology

DIMENSIONS

- 5.25" L x 2.5" W



DS2600WB



Intertek



LXC2-MR16

Directional Spot

DS2800WB/CB

MATERIAL / FEATURES

- Heavy duty cast brass
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- (CB) Carbon Black
 - CB cast brass fixtures finished with a superior top quality Dupont polyester powder coating
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 7.25" L x 2.5" W



DS2800WB



DS2800CB




Intertek



LXC2-MR16



LXC3-MR16



LXC5-MR16

Directional Spot

DS2800WB-LXC2

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2800WB-LXC2 includes:
 - DS2800WB cast brass WB finish spotlight
 - GS-1 ground stake
 - LXC2-MR16-FL-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16-FL-27K
- 9-15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 250 Lumens
- COB technology
- 7 year warranty

DIMENSIONS

- 7.25" L x 2.5" W



DS2800WB



Intertek



LXC2-MR16

Directional Spot

DS2905WB/CB

MATERIAL / FEATURES

- Heavy duty cast brass
- Adjustable / removable cowling for discrete lighting
- Shock and heat resistant convex glass lens
- Includes (GS1) ABS ground stake, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- (CB) Carbon Black
 - CB cast brass fixtures finished with a superior top quality Dupont polyester powder coating
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required
- DS2905WB - MR11 35 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LX2-MR11-27K

DIMENSIONS

- 4.25" L x 1.625" W



DS2905WB



LX2-MR11

Directional Spot

DS2905WB-LX2MR11

KITTED FIXTURE

PRODUCT DESCRIPTION

- The DS2905WB-LX2MR11 includes:
 - Cast brass WB finish spotlight
 - GS1 ground stake
 - LX2-MR11-27K LED lamp
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty
- LED lamp - 5 year warranty

LED LAMP INCLUDED

- LX2-MR11-27K
- 9 - 15 V AC/DC
- Constant current driver for long life
- FCC certified
- C ETL listed and approved
- 40 degree flood
- 2700K
- 240 Lumens
- COB technology

DIMENSIONS

- 4.25" L x 1.625" W



DS2905WB



LX2-MR11

Directional Spot

DS2336WB

MATERIAL / FEATURES

- Solid brass fixture housing
- Cast brass knuckle assembly
- Open faced no lens fixture
- Includes (GS1) ABS ground stake, ½" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Key screw on knuckle for easy adjustments
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3' - #18/2 direct bury landscape lighting wire with terminal spade connectors
- Lamp required - PAR36 75 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LVC4-PAR36
- LVC6-PAR36
- LVC8-PAR36

DIMENSIONS

- 4.53" W x 3.15" D x 9.25" L (from thread to tip of cowling)



DS2336WB



LVC4-PAR36



LVC6-PAR36



LVC8-PAR36



“HI” – Hybrid Integrated LED

Universal Lighting Systems strives for innovative design. Designing “HI” fixtures with integrated LED benefits and flexibility to replace damaged LED modules or upgrade them in the future.

UNVLS - crafting value through innovation.

Integrated LED Directional Spot

ILED-DS2025WB

MATERIAL / FEATURES

- Heavy duty cast brass
- Heat resistant glass lens
- Watertight sealed wire ingress grommet
- Brass Phillips head thumb screws on bracket for easy field adjustment
- Watertight sealed gasket
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- Includes two AC-102 silicone filled wire connectors
- Includes GS-mini ABS ground stake
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 25' submersible rated lighting wire lead
- Integrated LED - no lamp required
- Heat sinks for long life
- Low voltage transformer required (not included)
- C ETL listed and approved

LED - LIGHTING MODULE

- Integrated LED - no lamp required
- 282 Lumens , 3 W, 3.96 VA, .75 PF
- 2700 Kelvin temperature
- Beam spread - 70 degrees

DIMENSIONS

- 2" D x 2.75" W x 2.5"H



ILED-DS2025WB

