

Directional Spot

DSDL1350BK/WT

MATERIAL / FEATURES

- Heavy duty cast aluminum
- Cowling thumb set screw - allowing rotation of cowling
- Shock and heat resistant flat glass lens
- Includes three leg surface mount, 1/2" NPT thread, slotted for ease of installation
- EPDM rubber bug plug, prevents moisture/bugs from entering fixture
- Thumb screw on knuckle for easy field adjustment
- Double O ring seal for added moisture protection
- Weather resistant powder coat finish - aluminum
 - (BK) Black - DSDL1350BK
 - (WT) White - DSDL1350WT
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10 year warranty

ELECTRICAL

- 12 volt fixture
- 35' - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts, stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2, LXC3, LXC5
- LVC2, LVC3, LVC5

DIMENSIONS

- 9" L x 2.5" W



DSDL1350BK




DSDL1350WT



LXC2-MR16



LXC3-MR16



LXC5-MR16