

## SPECIFICATIONS

- Thermal plastic body
- Epoxy potted circuitry
- Par 36 terminal screw base
- 80+ CRI
- 35,000 hour rated
- Multiple beam spreads
- (FL) Flood 40°
- (WFL) Wide Flood 60°
- Stainless steel pins
- Made for use in enclosed fixtures and damp location
- 2700K AND 3000K temperature
- IP rating 67
- LVC4-PAR36
  - 400 Lumens, 5.5 Watts, .67 VA, .7 PF
- LVC6-PAR36
  - 600 Lumens, 7.5 Watts, .83 VA, .7 PF
- LVC8-PAR36
  - 800 Lumens, 11 Watts, 1.05 VA, .7 PF
- For use in open or enclosed fixtures
- Lamp - 5 year warranty

## ELECTRICAL

- 9-15 V AC/DC
- Constant current driver for long life
- Dimmable with Lutron magnetic dimmers
  - Dimming may reduce life span
- Fixture required (not included)
- Low voltage transformer or electronic transformer required (not included)
- C ETL listed and approved
- FCC certified

## MODELS

- LVC4-PAR36-FL-27K
- LVC4-PAR36-WF-27K
- LVC6-PAR36-FL-27K
- LVC6-PAR36-WF-27K
- LVC8-PAR36-FL-27K
- LVC8-PAR36-WF-27K
- LVC4-PAR36-FL-30K
- LVC4-PAR36-WF-30K
- LVC6-PAR36-FL-30K
- LVC6-PAR36-WF-30K
- LVC8-PAR36-FL-30K
- LVC8-PAR36-WF-30K

## DIMENSIONS

- LX2-MR11 - 1.375" W x 1.5" H



LVC4-PAR36



LVC6-PAR36



LVC8-PAR36

