

UW

Universal Well



Universal Well

UW8120BK

MATERIAL / FEATURES

- ABS well sleeve - black
- Includes clear plastic lens
- Includes stainless steel adjustable PAR 36 Gimbal
- Weathered brass covers (optional)
 - UC2940WB
 - Includes clear and optional frosted lens
 - UC2941WB
 - Includes clear and optional frosted louvered lens
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 3' - #18/2 direct bury landscape lighting wire with terminal spade connectors
- Lamp required - PAR36 75 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LVC2-PAR36
- LVC3-PAR36
- LVC5-PAR36

DIMENSIONS

- 5.5" W x 5.75" H on short side x 8" H on long side



UW8120BK



UC2940WB



UC2941WB



LVC2-PAR36



LVC3-PAR36



LVC5-PAR36

MATERIAL / FEATURES

- Injection molded poly glass body - black
- Water tight wire connector (underside)
- 25° adjustable bracket provides interior tilt for lamp
- Cast aluminum or cast brass cover required (not included)
- Includes two AC-102 silicone filled wire connectors
- Fixture - lifetime warranty

ELECTRICAL

- 12 volt fixture
- 3" - #18/2 direct bury landscape lighting wire
- HI-temp ceramic socket w/nickel contacts stainless steel springs, and Teflon jacketed wire leads
- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- C ETL listed and approved

LED LAMP OPTIONS

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps

DIMENSIONS

- 4.875" W x 4.5" H



UW6300BK



LXC2-MR16



LXC3-MR16



LXC5-MR16

Universal Well Covers

MATERIAL / FEATURES

- Heavy duty cast aluminum covers
 - UC1300BK/BZ
 - UC1301BK/BZ
 - UC1302BK/BZ
 - UC1306BK/BZ
 - 10 year warranty
- Heavy duty cast brass covers
 - UC2300WB/CB
 - UC2301WB/CB
 - UC2302WB
 - UC2306WB/CB
 - Lifetime warranty
- Stainless steel screws
- Shock and heat resistant glass lens
- EPDM rubber gasket
- Weather resistant powder coat finish - aluminum
 - (BK) Black
 - (BZ) Bronze
- (WB) Weathered Brass
 - WB Brass finish will patina / tarnish depending on environmental conditions
- (CB) Carbon Black
 - CB cast brass fixtures finished with a superior top quality Dupont polyester powder coating
- UW6300BK well light required (not included)

ELECTRICAL

- Lamp required - MR16 50 W Max
- Low voltage transformer required (not included)
- Wire connectors required (not included)
- C ETL listed and approved

DIMENSIONS

- UC1300BK/BZ - 4.375"W x .33"H
- UC1301BK/BZ - 4.375"W x .33"H
- UC1302BK/BZ - 4.375"W x 1.875"H
- UC1306BK/BZ - 4.375"W x 3"H
- UC2300WB/CB - 4.375"W x .33" H
- UC2301WB/CB - 4.375"W x .33" H
- UC2302WB - 4.375" W x 1.875" H
- UC2306WB/CB - 4.375" W x 3" H



UC1300BK*



UC1300BZ



UC1301BK*



UC1301BZ



UC1302BK*



UC1302BZ*



UC1306BK*



UC1306BZ*



UC2300WB



UC2301WB



UC2302WB



UC2306WB



UC2301CB



UC2300CB



UC2306CB

BRASS



ALUMINUM



*Arriving Fall 2023

KITTED FIXTURE

PRODUCT DESCRIPTION

- Kitted fixtures include cover and well - no lamp
 - UW1300BK - NL*
 - UW1300BZ - NL
 - UW1301BK - NL*
 - UW1301BZ - NL
 - UW1302BK - NL*
 - UW1302BZ - NL*
 - UW1306BK - NL*
 - UW1306BZ - NL*
- Kitted fixtures include cover, well and lamp
 - UW1300BK - LXC2*
 - UW1300BZ - LXC2
 - UW1301BK - LXC2*
 - UW1301BZ - LXC2
 - UW1302BK - LXC2*
 - UW1302BZ - LXC2*
 - UW1306BK - LXC2*
 - UW1306BZ - LXC2*
- Fixture - 10 year warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps



UW1300BK/BZ-NL



UW1300BK/BZ-LXC2



UW1301BK/BZ-NL



UW1301BK/BZ-LXC2



UW1302BK/BZ-NL



UW1302BK/BZ-LXC2



UW1306BK/BZ-NL



UW1306BK/BZ-LXC2

Recessed Light

ILED-RL BK SERIES

MATERIAL / FEATURES

- Integrated LED lighting fixture.
- Applications include core drilled installations in pavers, concrete, decks, steps, and downlights in soffits.
- Heat sink for maximum heat dissipation and life span.
- Thermal frosted lens to optimize even distribution of light.
- Heavy duty cast aluminum Dupont powder coated fixture.
- ABS plastic sleeve included for ease of installation.
- Stainless steel tension bar included for soffit applications.
- Watertight grommet to prevent moisture intrusion and provide strain relief
- Includes two AC-102 silicone filled wire connectors.
- Fixture - 10-year warranty

ELECTRICAL

- 12 volt fixture
- 10' 18/2 direct bury landscape lighting wire
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC Certified
- IP68

LED - LIGHTING MODULE

- LED module is completely encapsulated behind thermal glass lens
- COB Chipset technology
- ILED-RL1100BK-27K/30K
- ILED-RL1300BK-27K/30K
 - 100 Degree beam angle
 - 92 Lumen, 2.04 VA, 0.75 PF, 1.7 W
- ILED-RL1200BK-27K/30K
 - 60 Degree beam angle
 - 65 Lumen, 2.04 VA, 0.75 PF, 1.7 W
- ILED-RL1400BK-27K/30K
 - 115 Degree beam angle
 - 96 Lumen, 2.04 VA, 0.75 PF, 1.7 W

DIMENSIONS

- ILED-RL-1100/2100, Height 4.05", Width 1.89"
- ILED-RL-1200/2200, Height 1.31", Width 1.89"
- ILED-RL-1300/2300, Height 4.04", Width 2.25"
- ILED-RL-1400/2500, Height 5.14", Width 2.36", Depth 2.09"



ILED-RL1100BK-27K



ILED-RL1200BK-27K



ILED-RL1300BK-27K



ILED-RL1400BK-27K

Recessed Light

ILED-RL CB SERIES

MATERIAL / FEATURES

- Integrated LED lighting fixture
- Applications include core drilled installations in pavers, concrete, decks, steps, and downlights in soffits.
- Heat sink for maximum heat dissipation and life span.
- Thermal frosted lens to optimize even distribution of light
- Heavy duty cast brass with Dupont Carbon Black powder coated fixture.
- ABS plastic sleeve included for ease of installation.
- Stainless steel tension bar included for soffit applications.
- Watertight grommet to prevent moisture intrusion and provide strain relief
- Includes two AC-102 silicone filled wire connectors
- Fixture - 10-year warranty

ELECTRICAL

- 12-volt fixture
- 10' 18/2 direct bury landscape lighting wire
- Low voltage transformer required (not included)
- C ETL listed and approved
- FCC Certified
- IP68

LED - LIGHTING MODULE

- LED module is completely encapsulated behind thermal glass lens
- COB Chipset technology
- ILED-RL1100BK-27K/30K
- ILED-RL1300BK-27K/30K
 - 100 Degree beam angle
 - 92 Lumen, 2.04 VA, 0.75 PF, 1.7 W
- ILED-RL1200BK-27K/30K
 - 60 Degree beam angle
 - 65 Lumen, 2.04 VA, 0.75 PF, 1.7 W
- ILED-RL1400BK-27K/30K
 - 115 Degree beam angle
 - 96 Lumen, 2.04 VA, 0.75 PF, 1.7 W

DIMENSIONS

- ILED-RL-1100/2100 Height 4.05", Width 1.89"
- ILED-RL-1200/2200 Height 1.31", Width 1.89"
- ILED-RL-1300/2300 Height 4.04", Width 2.25"
- ILED-RL-1400/2500 Height 5.14", Width 2.36", Depth 2.09"



ILED-RL2100CB-27K



ILED-RL2200CB-27K



ILED-RL2300CB-27K



ILED-RL2400CB-27K

Universal Well

BRASS

KITTED FIXTURE

PRODUCT DESCRIPTION

- Kitted fixtures include cover and well - no lamp
 - UW2300WB - NL
 - UW2301WB - NL
 - UW2302WB - NL
 - UW2306WB - NL
- Kitted fixtures include cover, well and lamp
 - UW2300WB - LXC2
 - UW2301WB - LXC2
 - UW2302WB - LXC2
 - UW2306WB - LXC2
- Fixture - lifetime warranty
- LED lamp - 7 year warranty

LED LAMP INCLUDED

- LXC2-MR16 lamps
- LXC3-MR16 lamps
- LXC5-MR16 lamps



UW2300WB-NL



UW2300WB-LXC2



UW2301WB-NL



UW2301WB-LXC2



UW2302WB-NL



UW2302WB-LXC2



UW2306WB-NL



UW2306WB-LXC2