

LED - Wedge Base Series

LV1-T5, LV2-S8

SPECIFICATIONS

- Silica gel lamps
- G4 socket base
- 80+ CRI
- 25,000 hour rated
- UV infused inhibitors
- LED's are measured and tested at 12 Volts
 - Longest life occurs at 12 volts
- Silver soldering for long lasting performance
- Made for use in enclosed fixtures and damp location
- 2700K and 3000K color temperature
- LV1-T5WDG
 - 120 Lumens, 1.5 Watts, .13 VA, .7 PF
- LV2-T5WDG
 - 170 Lumens, 2.5 Watts, .17 VA, .7 PF
- LV2-S8WDG
 - 170 Lumens, 2.5 Watts, .17 VA, .7 PF
- IP rating 65
- Lamp - 5 year warranty

ELECTRICAL

- 9-15 V AC/DC
- Constant current driver for long life
- Dimmable with Lutron magnetic dimmers
 - Dimming may reduce life span
- Enclosed fixture required (not included)
- Low voltage transformer or electronic transformer required (not included)
- C ETL listed and approved
- FCC certified

MODELS

- LV1-T5WDG-27K
- LV1-T5WDG-30K
- LV2-T5WDG-27K
- LV2-T5WDG-30K
- LV2-S8WDG-27K
- LV2-S8WDG-30K

DIMENSIONS

- LV1-T5WDG - .5" W x 1.2" H
- LV2-T5WDG - .5" W x 1.2" H
- LV2-S8WDG - .9" W x 1.7" H



LV1-T5



LV2-S8

